Material Safety Data Sheet

Version 5.0 Revision Date 05/09/2012 Print Date 03/19/2013

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : *tert*-Butyllithium solution

Product Number : 186198 Brand : Aldrich

Supplier : Sigma-Aldrich

3050 Spruce Street SAINT LOUIS MO 63103

USA

Telephone : +1 800-325-5832 Fax : +1 800-325-5052 Emergency Phone # (For : (314) 776-6555

both supplier and

both supplier and manufacturer)

Preparation Information : Sigma-Aldrich Corporation

Product Safety - Americas Region

1-800-521-8956

2. HAZARDS IDENTIFICATION

Emergency Overview

OSHA Hazards

Flammable liquid, Pyrophoric, Target Organ Effect, Corrosive

Target Organs

Central nervous system, Heart, Lungs, Nerves.

GHS Classification

Flammable liquids (Category 2) Pyrophoric liquids (Category 1)

Substances, which in contact with water, emit flammable gases (Category 1)

Acute toxicity, Dermal (Category 5) Skin corrosion (Category 1B) Serious eye damage (Category 1)

Specific target organ toxicity - single exposure (Category 3)

Aspiration hazard (Category 1)
Acute aquatic toxicity (Category 2)

GHS Label elements, including precautionary statements

Pictogram

Signal word Danger

Hazard statement(s)

H225 Highly flammable liquid and vapour.

H250 Catches fire spontaneously if exposed to air.

H260 In contact with water releases flammable gases which may ignite spontaneously.

H304 May be fatal if swallowed and enters airways.

H313 May be harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H336 May cause drowsiness or dizziness.

H401 Toxic to aquatic life.

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P222 Do not allow contact with air.

P223 Keep away from any possible contact with water, because of violent reaction and

possible flash fire.

P231 + P232 Handle under inert gas. Protect from moisture.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/ physician.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

P422 Store contents under inert gas.

HMIS Classification

Health hazard: 3
Chronic Health Hazard: *
Flammability: 4
Physical hazards: 3

NFPA Rating

Health hazard: 3 Fire: 3 Reactivity Hazard: 3

Potential Health Effects

Inhalation May be harmful if inhaled. Material is extremely destructive to the tissue of the mucous

membranes and upper respiratory tract. Vapours may cause drowsiness and

dizziness.

Skin May be harmful if absorbed through skin. Causes skin burns.

Eyes Causes eye burns.

Ingestion May be harmful if swallowed. Aspiration hazard if swallowed - can enter lungs and

cause damage.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms : Lithium-2-methyl-2-propanide

t-BuLi

Formula : C₄H₉Li Molecular Weight : 64.06 g/mol

Component		Classification	Concentration
n-Pentane			
CAS-No. EC-No. Index-No.	109-66-0 203-692-4 601-006-00-1	Flam. Liq. 2; STOT SE 3; Asp. Tox. 1; Aquatic Chronic 2; H225, H304, H336, H411, EUH066	60 - 100 %
tert-Butyllithium			
CAS-No. EC-No.	594-19-4 209-831-5	Pyr. Liq. 1; Water-react. 1; Skin Corr. 1B; H250, H260, H314	10 - 30 %

For the full text of the H-Statements and R-Phrases mentioned in this Section, see Section 16

4. FIRST AID MEASURES

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

Aldrich - 186198 Page 2 of 8

In case of skin contact

Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Continue rinsing eyes during transport to hospital.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

5. FIREFIGHTING MEASURES

Suitable extinguishing media

Dry powderDry powder Carbon dioxide (CO2)

Extinguishing media which shall not be used for safety reasons

Water Carbon dioxide (CO2)Water

Special protective equipment for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

Hazardous combustion products

Hazardous decomposition products formed under fire conditions. - Carbon oxides, Lithium oxides

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). Do not flush with water.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

Conditions for safe storage

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Never allow product to get in contact with water during storage.

Recommended storage temperature: 2 - 8 °C

Air and moisture sensitive. Handle and store under inert gas. Sensitive to carbon dioxide

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value	Control	Basis
n-Pentane	109-66-0	TWA	600 ppm	USA. OSHA - TABLE Z-1 Limits for Air Contaminants -
	100 00 0		1,800 mg/m3	1910.1000
		STEL	750 ppm	USA. OSHA - TABLE Z-1 Limits for Air Contaminants -
			2,250 mg/m3	1910.1000
		TWA	1,000 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-1

Aldrich - 186198 Page 3 of 8

			2,950 mg/m3	Limits for Air Contaminants	
Remarks	The value in mg/m3 is approximate.				
		TWA	600 ppm	USA. ACGIH Threshold Limit Values (TLV)	
		TWA	600 ppm	USA. ACGIH Threshold Limit Values (TLV)	
	Peripheral	neuropathy	/		
		TWA	120 ppm 350 mg/m3	USA. NIOSH Recommended Exposure Limits	
	15 minute	ceiling valu			
		С	610 ppm 1,800 mg/m3	USA. NIOSH Recommended Exposure Limits	
	15 minute ceiling value				

Personal protective equipment

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. Protective gloves against thermal risks

Eye protection

Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection

Choose body protection according to the amount and concentration of the dangerous substance at the work place., Flame retardant protective clothing. Antistatic safety boots. Complete suit protecting against chemicals, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form liquid

Colour light yellow

Safety data

pH no data available

Melting no data available

point/freezing point

Boiling point no data available

Flash point -49 °C (-56 °F) - closed cup

Ignition temperature no data available
Autoignition no data available

Aldrich - 186198 Page 4 of 8

temperature

Lower explosion limit no data available
Upper explosion limit no data available
Vapour pressure no data available

Density 0.652 g/mL at 25 °C (77 °F)

Water solubility no data available Partition coefficient: no data available

n-octanol/water

Relative vapour no data available

density

Odour no data available
Odour Threshold no data available
Evaporation rate no data available

10. STABILITY AND REACTIVITY

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

Vapours may form explosive mixture with air.

Reacts violently with water.

Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight. Exposure to moisture.

Materials to avoid

acids, Water, Alcohols, Carbon dioxide (CO2), Humid air, Halogenated hydrocarbon, Amines

Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides, Lithium oxides Other decomposition products - no data available

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Oral LD50

no data available

Inhalation LC50 Dermal LD50

Other information on acute toxicity

no data available

Skin corrosion/irritation

no data available

Serious eye damage/eye irritation

Eyes: no data available

Respiratory or skin sensitization

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as

Aldrich - 186198 Page 5 of 8

probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a

known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

no data available

Teratogenicity

no data available

Specific target organ toxicity - single exposure (Globally Harmonized System)

no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System)

no data available

Aspiration hazard

no data available

Potential health effects

Inhalation May be harmful if inhaled. Material is extremely destructive to the tissue of the mucous

membranes and upper respiratory tract. Vapours may cause drowsiness and dizziness.

Ingestion May be harmful if swallowed. Aspiration hazard if swallowed - can enter lungs and cause

damage.

Skin May be harmful if absorbed through skin. Causes skin burns.

Eyes Causes eye burns.

Synergistic effects

no data available

Additional Information

RTECS: Not available

12. ECOLOGICAL INFORMATION

Toxicity

no data available

Persistence and degradability

no data available

Bioaccumulative potential

no data available

Mobility in soil

no data available

PBT and vPvB assessment

no data available

Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Toxic to aquatic life.

13. DISPOSAL CONSIDERATIONS

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 3394 Class: 4.2 (4.3) Packing group: I

Proper shipping name: Organometallic substance, liquid, pyrophoric, water-reactive (tert-Butyllithium)

Marine pollutant: No

Poison Inhalation Hazard: No

IMDG

UN number: 3394 Class: 4.2 (4.3) Packing group: I EMS-No: F-G, S-M

Proper shipping name: ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE (tert-

Butyllithium)

Marine pollutant: No

IATA

UN number: 3394 Class: 4.2 (4.3)

Proper shipping name: Organometallic substance, liquid, pyrophoric, water-reactive (tert-Butyllithium)

IATA Passenger: Not permitted for transport IATA Cargo: Not permitted for transport

15. REGULATORY INFORMATION

OSHA Hazards

Flammable liquid, Pyrophoric, Target Organ Effect, Corrosive

SARA 302 Components

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard, Reactivity Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

	CAS-No.	Revision Date
n-Pentane	109-66-0	2007-03-01
Pennsylvania Right To Know Components		
	CAS-No.	Revision Date
n-Pentane	109-66-0	2007-03-01
tert-Butyllithium	594-19-4	
New Jersey Right To Know Components		
	CAS-No.	Revision Date
n-Pentane	109-66-0	2007-03-01
tert-Butyllithium	594-19-4	

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

Aldrich - 186198 Page 7 of 8

Text of H-code(s) and R-phrase(s) mentioned in Section 3

Aquatic Chronic Chronic aquatic toxicity
Asp. Tox. Aspiration hazard

EUH066 Repeated exposure may cause skin dryness or cracking.

Flam. Liq. Flammable liquids

H225 Highly flammable liquid and vapour.

H250 Catches fire spontaneously if exposed to air.

H260 In contact with water releases flammable gases which may ignite spontaneously.

H304 May be fatal if swallowed and enters airways. H314 Causes severe skin burns and eye damage.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Pyr. Liq. Pyrophoric liquids Skin Corr. Skin corrosion

STOT SE Specific target organ toxicity - single exposure

Water-react. Substances, which in contact with water, emit flammable gases

Further information

Copyright 2012 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Aldrich - 186198 Page 8 of 8