## EASTMAN KODAK COMPANY -- 193 9628, KODAK PMT ACTIVATOR -- 6750-01-227-1125

```
========= Product Identification ============
Product ID:193 9628, KODAK PMT ACTIVATOR
MSDS Date:02/21/2001
FSC:6750
NIIN:01-227-1125
Status Code:A
MSDS Number: CLDWB
=== Responsible Party ===
Company Name: EASTMAN KODAK COMPANY
Address:343 STATE STREET
City:ROCHESTER
State:NY
ZIP:14650
Country:US
Info Phone Num:716-477-3194
Emergency Phone Num:716-722-5151
Preparer's Name: NOT PROVIDED
CAGE:19139
=== Contractor Identification ===
Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS
Address:343 STATE ST
Box:City:ROCHESTER
State:NY
ZIP:14650-1115
Country: US
Phone: 716-722-5151/(800) 242-2424
CAGE:19139
======= Composition/Information on Ingredients ========
Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Minumum % Wt:85.
Maxumum % Wt:90.
Other REC Limits: NOT PROVIDED
Code:F
Code:F
Ingred Name:SODIUM SULFITE
CAS:7757-83-7
RTECS #:WE2150000
Minumum % Wt:5.
Maxumum % Wt:10.
Other REC Limits: NOT PROVIDED
OSHA PEL:NOT PROVIDED
ACGIH TLV:NOT PROVIDED
Ingred Name: SODIUM THIOSULFATE
CAS:7772-98-7
RTECS #:XN6476000
Minumum % Wt:1.
Maxumum % Wt:5.
Other REC Limits: NOT PROVIDED
OSHA PEL:NOT PROVIDED
ACGIH TLV:NOT PROVIDED
Ingred Name: 2-METHYLAMINOETHANOL
CAS:109-83-1
RTECS #:KL6650000
Minumum % Wt:1.
Maxumum % Wt:5.
Other REC Limits: NOT PROVIDED
OSHA PEL:NOT PROVIDED
ACGIH TLV:NOT PROVIDED
Ingred Name:GLYCERIN
CAS:56-81-5
RTECS #:MA8050000
Minumum % Wt:1.
Maxumum % Wt:5.
```

Other REC Limits: NOT PROVIDED

OSHA PEL:15 MG/M3 ACGIH TLV:10 MG/M3

Ingred Name:HYDROQUINONE
CAS:123-31-9
RTECS #:MX3500000
< Wt:1.
Other REC Limits:NOT PROVIDED
OSHA PEL:2 MG/M3
ACGIH TLV:2 MG/M3
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB</pre>

======= Hazards Identification ===========

LD50 LC50 Mixture:NOT PROVIDED

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EFFECTS OF EXPOSURE: INHALATION:
EXPECTED TO BE LOW HAZARD FOR RECOMMENDED HANDLING. IN CONTACT WITH
STRONG ACIDS OR IF HEATED, SULFITES MAY LIBERATE SULFUR DIOXIDE
GAS. SULFUR DIOXIDE GAS IS IRRITATI NG TO RESPIRATORY TRACT.
ASTHMATICS OR HYPERSENSITIVE INDIVIDUALS MAY EXPERIENCE DIFFICULT
BREATHING. EYES: CAUSES IRRITATION. SKIN: CAUSES IRRITATION. MAY
CAUSE ALLERGIC SKIN REACTION BASED ON HUMAN EXPERIENCE. INGESTION:
MAY BE HARMFUL IF SWALLOWED. ASTHMATICS OR SULFITE-SENSITIVE
INDIVIDUALS MAY EXPERIENCE WHEEZING, CHEST TIGHTNESS, STOMACH
UPSET, HIVES, FAINTNESS, WEAKNESS AND DIARRHEA. MAY CA USE
IRRITATION OF GASTROINTESTINAL TRACT

- Explanation of Carcinogenicity:CARCINOGENICITY CLASSIFICATION
  (COMPONENTS PRESENT AT 0.1% OR MORE): INTERNATIONAL AGENCY FOR
  RESEARCH ON CANCER (IARC): NONE AMERICAN CONFERENCE OF GOVERNMENTAL
  INDUSTRIAL HYGIENISTS (ACGIH): NONE NA TIONAL TOXICOLOGY PROGRAM
  (NTP): NONE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA):
  NONE
- Effects of Overexposure:INHALATION: IN CONTACT WITH STRONG ACIDS OR IF HEATED, SULFITES MAY LIBERATE SULFUR DIOXIDE GAS. SULFUR DIOXIDE GAS IS IRRITATING TO RESPIRATORY TRACT. EYES: CAUSES IRRITATION. SKIN: CAUSES IRRITATION . MAY CAUSE ALLERGIC SKIN REACTION BASED ON HUMAN EXPERIENCE. INGESTION: MAY CAUSE IRRITATION OF GASTROINTESTINAL TRACT
- Medical Cond Aggravated by Exposure:SOME ASTHMATICS, HYPERSENSITIVE OR SULFITE-SENSITIVE INDIVIDUALS MAY EXPERIENCE DIFFICULT BREATHING, WHEEZING, CHEST TIGHTNESS, STOMACH UPSET, HIVES, FAINTNESS, WEAKNESS AND DIARRHEA.

First Aid:INHALATION: IF SYMPTOMATIC, MOVE TO FRESH AIR. TREAT SYMPTOMATICALLY. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTEN TION IF SYMPTOMS OCCUR. SKIN: WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND SHOES. IF SKIN IRRITATION OR AN ALLERGIC SKIN REACTION DEVELOPS, GET MEDICAL ATTENTION. WASH CONTAMINATED CLOTH ING BEFORE REUSE. DESTROY OR THOROUGHLY CLEAN CONTAMINATED SHOES. INGESTION: DRINK 1-2 GLASSES OF WATER. SEEK MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

======== Fire Fighting Measures ===========

Flash Point:NONE

Extinguishing Media:USE APPROPRIATE AGENT FOR ADJACENT FIRE.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND
PROTECTIVE CLOTHING. FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS
DECOMPOSITION PRODUCTS.

Unusual Fire/Explosion Hazard:NONE.

======= Accidental Release Measures =========

Spill Release Procedures:FLUSH TO SEWER WITH LARGE AMOUNT OF WATER.
OTHERWISE, ABSORB SPILL WITH VERMICULITE OR OTHER INERT MATERIAL,
THEN PLACE IN A CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE
THOROUGHLY TO REMOVE RESIDUAL C ONTAMINATION.

Neutralizing Agent:NOT PROVIDED

========= Handling and Storage ==========

```
Handling and Storage Precautions: KEEP CONTAINER CLOSED. KEEP AWAY FROM
    INCOMPATIBLE SUBSTANCES
```

Other Precautions: AVOID BREATHING MIST OR VAPOR. AVOID CONTACT WITH EYES, SKIN, AND CLOTHING. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. THE ROUTINE USE OF A NONALKALINE (ACID) TYPE OF HAND CLEANER AND REGULAR CLEANING OF WORKING SURFACES, GLOVES, ETC. WILL HELP MINIMIZE THE POSSIBILITY OF A SKIN REACTION.

====== Exposure Controls/Personal Protection =========

Respiratory Protection: NONE SHOULD BE NEEDED. A RESPIRATOR SHOULD BE WORN IF HAZARDOUS DECOMPOSITION PRODUCTS ARE LIKELY TO BE OR HAVE BEEN RELEASED. RESPIRATOR TYPE: ACID GAS. SEE STABILITY AND REACTIVITY SECTION. IF RESPI RATORS ARE USED, A PROGRAM SHOULD BE INSTITUTED TO ASSURE COMPLIANCE WITH OSHA STANDARD 29 CFR 1910.134.

Ventilation: GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES PER HOUR) SHOULD BE USED. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS.

Protective Gloves: WEAR IMPERVIOUS GLOVES AND PROTECTIVE CLOTHING APPROPRIATE FOR RISK OF EXPOSURE

Eye Protection: WEAR SAFETY GLASSES WITH SIDE SHIELDS (OR GOGGLES). Other Protective Equipment: EYE BATH, SAFETY SHOWER, WASHING FACILITIES Work Hygienic Practices:IT IS A GOOD INDUSTRIAL HYGIENE PRACTICE TO MINIMIZE EYE CONTACT. IT IS A GOOD INDUSTRIAL HYGIENE PRACTICE TO MINIMIZE SKIN CONTACT.

Supplemental Safety and Health

ABBREVIATION: N/A = NOT APPLICABLE. N/AV = NOT AVAILABLE. N/K = UNKNOWN. N/P = NOT PROVIDED. N/R = NOT RELEVANT. N/D = NOT DETERMINED. N/E = NOT ESTABLISHED. CNS = CENTRAL NERVOUS SYSTEM. GI = GASTROI NTESTINAL. SCBA = SELF CONTAINED BREATHING APPARATUS.

======= Physical/Chemical Properties ==========

NRC/State Lic Num: NOT RELEVANT

Boiling Pt:>100.C, 212.F

Melt/Freeze Pt:M.P/F.P Text:NOT PROVIDED Decomp Temp:Decomp Text:NOT PROVIDED Vapor Pres:68F: 24 MBAR (18 MM HG)

Vapor Density:0.6 Spec Gravity:1.076

pH:11.0

Viscosity:NOT PROVIDED

Evaporation Rate & Reference:NOT PROVIDED

Solubility in Water: COMPLETE

Appearance and Odor:LIGHT ORANGE, ODORLESS, LIQUID.

Percent Volatiles by Volume:95 WT

Corrosion Rate:NOT PROVIDED

======= Stability and Reactivity Data ===========

Stability Indicator/Materials to Avoid:YES STRONG ACTDS. Stability Condition to Avoid:NOT PROVIDED Hazardous Decomposition Products:SULFUR DIOXIDE.

====== Toxicological Information ==========

Toxicological Information: EFFECTS OF EXPOSURE: INHALATION: EXPECTED TO BE LOW HAZARD FOR RECOMMENDED HANDLING. IN CONTACT WITH STRONG ACIDS OR IF HEATED, SULFITES MAY LIBERATE SULFUR DIOXIDE GAS. SULFUR DIOXIDE GAS IS IRRITATI NG TO RESPIRATORY TRACT. ASTHMATICS OR HYPERSENSITIVE INDIVIDUALS MAY EXPERIENCE DIFFICULT BREATHING. EYES: CAUSES IRRITATION. SKIN: CAUSES IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION BASED ON HUMAN EXPERIENCE. INGESTION: MAY BE HARMFUL IF SWALLOWED. ASTHMATICS/ SULFITE-SENSITIVE INDIVIDUALS MAY EXPERIENCE WHEEZING, CHEST TIGHTNESS, STOMACH UPSET, HIVES, FAINTNESS, WEAKNESS AND DIARRHEA. MAY CAUS E IRRITATION OF GASTROINTESTINAL TRACT

======= Ecological Information ==========

Ecological: THE FOLLOWING PROPERTIES ARE ESTIMATED FROM THE COMPONENTS OF THE PREPARATIONS. POTENTIAL TOXICITY: FISH LC50 MG/L: 10-100. DAPHNID EC50 MG/L: 1-10. ALGAL IC50 MG/L: >100. ORGANICS READILY DEGR ADABLE (>70%): YES (7 DAYS). POTENTIAL BIOACCUMULATION: LOG POW <1. COD (APPROXIMATE G/L): 115. BOD5 (APPROXIMATE G/L): 79. POTENTIAL TOXICITY: WASTE TREATMENT MICROORGANISMS EC50 (MG/L): >100.

====== Disposal Considerations ==========

Waste Disposal Methods:DISCHARGE, TREATMENT, OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE, OR LOCAL LAWS. FLUSH TO SEWER WITH LARGE AMOUNT OF WATER. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE, FOLLOW LABEL WARNINGS EV EN AFTER CONTAINER IS EMPTIED.

======= MSDS Transport Information =========

Transport Information: FOR TRANSPORTATION INFORMATION REGARDING THIS PRODUCT CALL THE KODAK WORLDWIDE TRANSPORTATION HAZMAT HOT LINE: (716) 722-2400 BETWEEN 8 A.M. AND 5 P.M. (EASTERN STANDARD TIME), MONDAY THROUGH FRIDAY .

======= Regulatory Information ==============

SARA Title III Information: CHEMICAL(S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OR TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT (SARA) OF 1986 AND 40 CFR PART 372: NONE.

Federal Regulatory Information: NOT PROVIDED State Regulatory Information: MATERIAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER: NONE MATERIAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE ADVERSE REPRODUCTIVE EFFECTS: NONE

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.